



NOTE:

1. DETECTABLE WARNING SHALL CONSIST OF RAISED TRUNCATED DOMES WITH A DIAMETER OF 0.9", A HEIGHT OF NOMINAL 0.2", AND A CENTER-TO-CENTER SPACING OF NOMINAL 2.35", AND SHALL CONTRAST VISUALLY WITH ADJOINING SURFACES, ACHIEVED BY THE INSTALLATION OF ARMOR TILE ADA-C-2436, ADA-C-2448 OR ADA-C-2460 (OR APPROVED EQUAL) AND SHALL BE AN INTEGRAL PART OF THE WALKING SURFACE.
2. STAMPED CONCRETE IS NOT AN APPROVED EQUAL.
3. DOWNTOWN DETECTABLE WARNINGS MAY BE ADA 2004 COMPLIANT DETECTABLE WARNING PAVERS.
4. DETECTABLE WARNING PLATS ARE TO BE COLONIAL RED IN COLOR OR APPROVED EQUAL.
5. DETECTABLE WARNING SURFACES SHALL BE 24" WIDE AND EXTEND THE FULL LENGTH OF THE PUBLIC USE AREA.

<i>JLB</i>	1/1/12
Approved	Date
Revisions	



DETECTABLE WARNING

435.01